



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/729,752

12/04/2003

Loren Dean

MWS-034RCE

3180

74321

7590

12/30/2008

LAHIVE & COCKFIELD, LLP/THE MATHWORKS
FLOOR 30, SUITE 3000
One Post Office Square
Boston, MA 02109-2127

EXAMINER

TRUONG, LECHI

ART UNIT

PAPER NUMBER

2194

MAIL DATE

DELIVERY MODE

12/30/2008

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/729,752	Applicant(s) DEAN ET AL.	
	Examiner LECHI TRUONG	Art Unit 2194	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 11/28/2008.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☐ Claim(s) 1,3-6 and 10-46 is/are pending in the application.
4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1, 3-6, 10-46 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

1. Claims 1, 3-6, 10-46 are presented for the examination. Claims 2, 7-9 are cancelled.

Claim Rejections - 35 USC § 112

2. Claims 1-31 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.

3. Claims 1, 10, recite the feature “physical connection” which was not described in the specification.

Claim Objections

4. Claims 32-37 are objected to because of the following informalities: There is an error on the phrase “readable medium”. Appropriate correction is required to change from “readable medium” to “readable storage medium”.

5. Claim 7 is objected to because of the following informalities: There is an error on the phrase “comprising,” Appropriate correction is required to change from “comprising,” to “comprising:”

Claim Rejections - 35 USC § 103

Art Unit: 2194

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. Claim **1, 3-6** are rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US Patent 5,926,775) in view of Tuatini(US 2001/0047385 A1) and further in view of Bryant(US 5,764,546 A).

As to claim 1, Brumley teaches an electronic device (the computer 102 running an operating system... provide field electrical, col 5, ln 33-38), an image acquisition device, a DAQ device, col 5, ln 33-38), the electrical device independent of an interface protocol of the image acquisition device (the generic functionality which is generic to or independent of a number of DAQ devices or boards, i.e., is independent of a family of devices, col 9, ln 34-38/ plurality of mini-driver primitives each perform a portion of controlling the DAQ device, i.e., each of the plurality of mini-driver primitives perform operations to control specific resources of the DAQ device, col 3, ln 65-67 to col 4, ln 1-3/ The interpreter operates to configure device family independent or hardware independent features , for each device, col 4, ln 20-25), a request from the user (calls from the DAQ user application, col 3, ln 7-9), receiving a request from a requester to access the image acquisition device, col 3, ln 7-9/ col 27, ln 20-25), establishing a communication channel with the image acquisition device(col 12, ln 5-15/ Fig. 7), accessing a

Art Unit: 2194

feature of the image acquisition device using the communication channel(col 6, ln 1-5), the request specifies a format for a response from the image acquisition (col 10, ln 56-67).

Brumley does not teaches to receiving the response in the specified format which specified by the request. However, Tuatini teaches receiving the response in the specified format(client system 320 requests services of an application program by sending request messages in a client-specific format to the application program, and receives results of the services in response messages in a client-specific format, para[0066], ln 1-3).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley with Tuatini to incorporate the feature of receiving the response in the specified format which specified by the request because this provides the flexibility needed by a group to provide applications tailored to their customers, and that would help to reduce the cost of developing and maintaining the applications.

Brumley and Tuatini do not teach establishing a communication channel with a hardware interface of the image acquisition device, configuring physical connection of the image acquisition device supported by the hardware. However, Bryant teaches establishing a communication channel with a hardware interface of the acquisition device, configuring physical connection of the acquisition device supported by the hardware(A typical DAQ system comprises a computer system with DAQ hardware, one or more transducers, and possibly signal conditioning logic coupled between the transducers and the DAQ hardware col 1, ln 19-25/ For an analog input channel, this input is preferably received using a "DAQ Hardware Panel", col 8, ln 60-65/ The DAQ Hardware panel in the Analog Input Configuration dialog box of FIG. 8 is used to select which DAQ device (DAQ plug-in board, stand-alone DAQ product, or SCXI

Art Unit: 2194

module) and which channel on the device the user is assigning to this channel configuration, col 16, ln 15-22) .

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley and Tuatini with Bryant to incorporate the features of establishing a communication channel with a hardware interface of the image acquisition device, configuring physical connection of the image acquisition device supported by the hardware because this provides a simpler and more convenient mechanism for configuring DAQ channels in a DAQ instrumentation system.

As to claim 3, Brumley teaches communication with an interface of the image acquisition device to establish communication (col 11, ln 31-36), establishing one or more communication procedures for communication with the image acquisition device (col 11, ln 31-37), and the communication procedures providing instruction on how data transfers are managed across the communication channel (col 27, ln 24-34).

As to claim 4, Brumley teaches the one or more communication procedures provides instructions for at least one of, logging data to file, buffering data received from the image acquisition device, generating events, and translating error codes from the image acquisition device (col 3, ln 14-20).

As to claim 5, Brumley teaches the requester is received from a user interface (col 3, ln 9-13).

As to claim 6, Brumley teaches user interface comprises an object-based interface having methods and attributes (col 13, ln 21-30).

Art Unit: 2194

7. Claims **10-14, 19-25, 30** are rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US Patent 5, 926775) in view of Beck (US 20040088349 A1) and further in view of Bryant(US 5764546 A).

As to claim 10, Brumley teaches a first communication link between a user of the electronic device and an image acquisition engine (the interpreter performing DAQ driver level functions in response to receiving the call from the DAQ user application, col 27, ln 60-65), establishing a second communication link between the image acquisition engine and an interface of the selected image acquisition device (the interpreter generating calls to a plurality of mini-driver primitives in response to receiving the call from the DAQ user application; the plurality of mini-driver primitives each performing a portion of controlling the DAQ device, col 27, ln 25-30), the selected image acquisition device to allow the user to communication with the selected image acquisition device(col 3, ln 34-40/ col 11, ln 1-5).

Brumley does not teach the image acquisition engine generating a response in a user-specified format. However, Beck teaches the engine generating a response in a user-specified format (the Web server requests the ISP to perform an action, which consists of providing information about the end-user's Internet access device and access link bandwidth. After the ISP responds to the Web server with that information, it uses that information to formulate its response to end-user's original request in a format appropriate for that end-user's client type, para [0032], ln 6-12).

Art Unit: 2194

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley with Beck to incorporate the feature of the engine generating a response in a user-specified format because this performs the requested user-specific action and provides the Web server with information relating to the result of the requested action.

Brumley and Beck do not teach establishing a communication channel with a hardware interface of the image acquisition device, configuring physical connection of the image acquisition device supported by the hardware. However, Bryant teaches establishing a communication channel with a hardware interface of the acquisition device, configuring physical connection of the acquisition device supported by the hardware(A typical DAQ system comprises a computer system with DAQ hardware, one or more transducers, and possibly signal conditioning logic coupled between the transducers and the DAQ hardware col 1, ln 19-25/ For an analog input channel, this input is preferably received using a "DAQ Hardware Panel", col 8, ln 60-65/ The DAQ Hardware panel in the Analog Input Configuration dialog box of FIG. 8 is used to select which DAQ device (DAQ plug-in board, stand-alone DAQ product, or SCXI module) and which channel on the device the user is assigning to this channel configuration, col 16, ln 15-22) .

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley and Beck with Bryant to incorporate the features of establishing a communication channel with a hardware interface of the image acquisition device, configuring physical connection of the image acquisition device supported by the hardware

Art Unit: 2194

because this provides a simpler and more convenient mechanism for configuring DAQ channels in a DAQ instrumentation system.

As to claim 11, Brumley teaches associating the image acquisition engine with a driver adapter for communicating with the interface of the selected image acquisition device (col 3, ln 34-40).

As to claim 12, Brumley teaches selecting the image acquisition device from a plurality of image acquisition devices associated with electronic device (col 11, ln 1-5).

As to claim 13, Brumley teaches abstracting a representation of the selected image acquisition device for use in establishing the second communication link by using the information provided by the driver (col 27, ln 29-33).

As to claim 14, Brumley teaches rendering on a display device of the electronic device a user interface for use by the user for interfacing with the image acquisition engine, (col 7, ln 24-34).

As to claim 19, Brumley teaches requesting the image acquisition engine to determine each interface associated with an image acquisition device installed an accessible to image engine, (col 3, and ln 34-40).

As to claim 20, Brumley teaches determine each interface associated with an image acquisition engine installed an accessible to image engine (col 3, ln 34-40).

As to claim 21, Brumley teaches one or more image acquisition device types (col 3, ln 48-52).

Art Unit: 2194

As to claim 22, Brumley teaches providing the image acquisition engine with one or more request for configuring the selected image acquisition device (col 3, ln 55-67).

As to claim 23, Brumley teaches configuring the selected image acquisition device based on each provided request (col 11, ln 1-6).

As to claim 24, Brumley teaches configuring a type of image acquisition based on each provided request (col 11, ln 1-6).

As to claim 25, Brumley teaches the type of image acquisition comprises still image acquisition (col 11, ln 1-6).

As to claim 30, Brumley teaches the image acquisition engine is capable of feeding to the user one or more live images from the selected image acquisition device (col 7, ln 24-30).

9. Claims **15, 16, 18, 26-29** are rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US. Patent 5, 926775) in view of Beck (US 20040088349 A1) of Bryant(US 5764546 A) and further in view of MacDonald (US 6,614916 B2)

As to claim 15, Brumley , Beck and Bryant do not teach triggering the image acquisition device on a selected event to acquire one or more image. However, MacDonald teaches image acquisition device on a selected event to acquire one or more image (machine vision system 100 triggers acquisition of a full frame image of a feature of interest 112 when the feature 112 is within the field of view 114 of video camera 102, col 4, and ln 44-48).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley, Beck and Bryant with MacDonald to incorporate

Art Unit: 2194

the feature of image acquisition device on a selected event to acquire one or more image because this avoids at least some of the difficulties associated with conventional triggering methods.

As to claim 16, MacDonald teaches previewing one of more images from the image acquisition device before, while or after the triggering of the image acquisition device occurs (col 3, ln 25-36).

As to claim 18, MacDonald teaches identifying a region of interest for an image acquired by the image acquisition device (col 6, ln 5-11).

As to claims 26, 27, 28, 29, MacDonald teaches image acquired in a sequence, number of images a single image, a plurality of images (col 4, ln 5-60/ col 3, ln 1-3/ col 4, ln 40-45/ col 5, ln 1-5).

10. Claims **17** and **31** **are** rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US. Patent 5, 926775) in view of Beck (US 20040088349 A1) in view of Bryant(US 5764546 A) and further in view of Casini (US. Patent 5, 201027).

As to claim 31, Brumley , Beck and Bryant do not teach defining a color space for the images acquired by the image acquisition device. However, Casini teaches defining a color space for the images acquired by the image acquisition device (select the fundamental colors, change them and partially superimpose them, with simultaneous on screen display or printout on paper, col 3, ln 23-26).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley , Beck and Bryant with Casini to incorporate the

Art Unit: 2194

feature of defining a color space for the images acquired by the image acquisition device because this allows the system to perform possible variations in the design and in the number of colors which simultaneously direct on-screen display.

As to claim 17, Casini teaches images from the image acquisition device on a display (col 3, ln 39-43).

11. Claims **32-42** are rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US Patent 5,926775) in view of Trsar(US 5778328 A) and further in view of Tran(US 20040119620).

As to claim 32, Brumley teaches an electronic device (the computer 102 running an operating system... provide field electrical, col 5, ln 33-38), an image acquisition device, a DAQ device, col 5, ln 33-38), the electrical device independent of an interface protocol of the image acquisition device (the generic functionality which is generic to or independent of a number of DAQ devices or boards, i.e., is independent of a family of devices, col 9, ln 34-38/ plurality of mini-driver primitives each perform a portion of controlling the DAQ device, i.e., each of the plurality of mini-driver primitives perform operations to control specific resources of the DAQ device, col 3, ln 65-67 to col 4, ln 1-3/ The interpreter operates to configure device family independent or hardware independent features , for each device, col 4, ln 20-25), receiving a request from a requester to access the image acquisition device, col 3, ln 7-9/ col 27, ln 20-25), creating a communication channel with the image acquisition device(col 12, ln 5-15/ Fig. 7), accessing a feature of the image acquisition device using the communication channel(col 6, ln 1-

Art Unit: 2194

5), teaches the request specifies a format for a response from the image acquisition (col 10, ln 56-67).

Brumley does not teach providing information on available types of triggers supported by the image acquisition device. However, Trsar teaches providing information on available types of triggers supported by device(The engine analyzer 10 supports all of the three standard types of triggering for digital display scopes in engine analyzers , col 4, ln 28-32/ This Trigger Check routine first checks at 71 to see if signal triggering has been selected in the icon box 40a. If it has not, this means that auto triggering is selected, since this is the only other type of triggering is selected, since this is the only other type of triggering available in this mode, so the program then at 72 marks the start of the frame as the trigger location and then indicates, at 73, that a trigger has been found and returns at 74 to the decision 59 in the routine of FIG. 5., col 7, ln 3-11).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley with Trsar to incorporate the feature of providing information on available types of triggers supported by device because this controllers the acquisition and display of a high-voltage secondary ignition signal waveform and provides the user selection of the sweep and trigger modes.

Brumley and Trsar do not teach one of a plurality of image acquisition devices, the plurality of image acquisition devices implementing a plurality of different acquisition technologies, automatically determining available types of triggers supported by a particular acquisition device. However, Tran teaches one of a plurality of image acquisition devices, the plurality of image acquisition devices implementing a plurality of different acquisition technologies, automatically determining available types of triggers supported by a particular

Art Unit: 2194

acquisition device (different types of acquisition devices may be used, para [0012], ln 8-10/to one or more of the input channels to acquire data of a specific type. DSOs also provide a full range of analog triggering functions such as, rising edge, pulsewidth, and runt triggering, Para[0002], ln 7-10/Each of the acquisition devices 110.sub.1 through 110.sub.N produces a respective trigger enable signal TE.sub.1 through TE.sub.N. Each of the produced trigger signals TE.sub.1 through TE.sub.N is, para[0019], ln 7-14/The above-described system 100 of FIG. 1 provides for a plurality of data acquisition devices 110, where each acquisition device provides a respective trigger signal determined according to the decoding or detection of sequential and/or logical conditions of its respective input channels, as well as detection of analog signal conditions, para[0022], ln 1-7/ an analog trigger circuit 109 receives the analog signals under test and provides a trigger output signal TA to the first 111 and second 112 event decoders upon detection of a preselected analog signal condition, para[0014], ln 7-12/The first event decoder 111 processes one or more of the received input channel data streams CH1-4 according to a combinational and/or sequential logic function to determine whether a predefined triggering condition exists, Para[0019], ln 1-5/ The second event decoder 112 preferably decodes or determines the occurrence of the same triggering event and responsively produces a triggering signal T adapted to control the acquisition unit 113, para[0029], ln 6-10).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley and Trsar with Tran to incorporate the feature of one of a plurality of image acquisition devices, the plurality of image acquisition devices implementing a plurality of different acquisition technologies, automatically determining available types of triggers supported by a particular acquisition device because this provides a

Art Unit: 2194

signal acquisition triggering using multiple signal acquisition devices and/or multiple input channels .

As to claim 33, Brumley teaches the request specifies format for a response from the image acquisition device (col 10, ln 56-67).

As to claim 34, Brumley teaches communication with an interface of the image acquisition device to establish communication (col 11, ln 31-36), establishing one or more communication procedures for communication with the image acquisition device (col 11, ln 31-37), and the communication procedures providing instruction on how data transfers are managed across the communication channel (col 27, ln 24-34).

As to claim 35, Brumley teaches the one or more communication procedures provides instructions for at least one of, logging data to file, buffering data received from the image acquisition device, generating events, and translating error codes from the image acquisition device (col 3, ln 14-20).

As to claim 36, Brumley teaches the requester is received from a user interface (col 3, ln 9-13).

As to claim 37, Brumley teaches user interface comprises an object-based interface having methods and attributes (col 13, ln 21-30).

As to claim 38, it is an apparatus claim of claim 32; therefore, it is rejected for the same reason as claim 32 above.

As to claim 39, Brumley teaches associating the image acquisition engine with a driver adapter for communicating with the interface of the selected image acquisition device (col 3, ln 34-40).

Art Unit: 2194

As to claim 40, Brumley teaches selecting the image acquisition device from a plurality of image acquisition devices associated with electronic device (col 11, ln 1-5).

As to claim 41, Brumley teaches abstracting a representation of the selected image acquisition device for use in establishing the second communication link by using the information provided by the driver (col 27, ln 29-33).

As to claim 42, Brumley teaches rendering on a display device of the electronic device a user interface for use by the user for interfacing with the image acquisition engine, (col 7, and ln 24-34).

12. Claims **43, 44, 46** are rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US. Patent 5, 926775) in view of Trsar (US 5778328 A), as applied to claim 32 above, in view of MacDonald (US 6,614916 B2) and further in view of Tran(US 20040119620).

As to claim 43, Brumley , Trsar, Tran do not teach triggering the image acquisition device on a selected event to acquire one or more image. However, MacDonald teaches image acquisition device on a selected event to acquire one or more image (machine vision system 100 triggers acquisition of a full frame image of a feature of interest 112 when the feature 112 is within the field of view 114 of video camera 102, col 4, and ln 44-48).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley , Trsar and Tran with MacDonald to incorporate

Art Unit: 2194

the feature of image acquisition device on a selected event to acquire one or more image because this avoids at least some of the difficulties associated with conventional triggering methods.

As to claim 44, MacDonald teaches previewing one of more images from the image acquisition device before, while or after the triggering of the image acquisition device occurs (col 3, ln 25-36).

As to claim 46, MacDonald teaches identifying a region of interest for an image acquired by the image acquisition device (col 6, ln 5-11).

13. Claim **45** is rejected under 35 U.S.C. 103(a) as being unpatentable over Brumley et al (US. Patent 5, 926775) in view of Trsar (US 5778328 A), as applied to claim 32 above, in view of Casini (US. Patent 5,201027) and further in view of Tran(US 20040119620).

.

As to claim 45, Brumley , Trsar and Tran do not teach images from the image acquisition device on a display (col 3, ln 39-43). However, Casini teaches images from the image acquisition device on a display (col 3, ln 39-43).

It would have been obvious to one of the ordinary skill in the art at the time the invention was made to modify the teaching of Brumley, Trsar and Tran with Casini to incorporate the feature of mages from the image acquisition device on a display because this allows the system to perform possible variations in the design and in the number of colors which simultaneously direct on-screen display.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to LeChi Truong whose telephone number is (571) 272-3767. The examiner can normally be reached on 8 - 5.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Meng-Ai An can be reached on (571) 272-3756. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIP. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIP system, contact the Electronic Business Center (EBC) at 866-217-9197(toll-free).

/LeChi Truong/

Examiner, Art Unit 2194